

Rugged with Feather-Touch Disassembly



REVO[®] 2.0

4-Wheel Scooter




Feather-touch disassembly

Experience the Revo 2.0[®], a new class of scooter that combines an array of features into one great package. Built to last, the Revo 2.0 offers the rugged dependability you expect from luxury mid-size scooters. Advanced Comfort-Trac Suspension (CTS), feather-touch disassembly and standard under seat storage add to this durable and stylish scooter. Ride on with the Revo 2.0!

MOVE
MOBILITY
movemobility.com.au

Revo 2.0

Specifications

Weight Capacity	170 kgs (375 lbs.)
Maximum Speed ¹	Up to 8 km/h (5 mph)
Ground Clearance ³	3.2 cm (1.25") at transaxle
Turning Radius ³	132.1 cm (52")
Overall Length ³	119.4 cm (47")
Overall Width ³	52.7 cm (20.75")
Front Tyres	7.6 x 22.9 cm (3" x 9")
Rear Tyres	7.6 x 22.9 cm (3" x 9")
Range Per Charge ^{1,2}	Up to 21 km (13 miles)
Total Weight Without Batteries ⁵	60 kg (132 lbs.)
Heaviest Piece When Disassembled ³	25.9 kg (57 lbs.) (front section)
Standard Seating	Type: Foldable, molded plastic Material: Black vinyl Dimensions: Width: 50.8 cm (20") Depth: 45.7 cm (18")
Suspension	Front and rear
Brakes	Regenerative and electro-mechanical
Battery Requirements ^{3,5}	(2) U1 batteries Weight: 11.5 kg (25 lbs.) each
Battery Charger	Off-board, 3.5 amp
Delta Tiller	Yes
Colour Options	

Features

- USB charging port built into the tiller
- Durable and stylish rear bumper
- CTS front and rear suspension
- Delta tiller, ergonomic wraparound handles
- Pride's exclusive black, flat-free non-scuffing tyres
- Feather-touch disassembly
- Front basket
- Under seat storage
- Easily accessible tie down points (for transport of unoccupied scooter)
- User-friendly 8.89 cm (3.5") under-deck clearance at side deck



Accessories

- Pride rear bag/walking stick holder
- Walker holder*
- Oxygen tank holder*
- Mobile Phone holder
- Cup holder
- Rear view mirror
- Saddle bag

****Must have Pride rear bag to attach**

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tyre condition.

This specification can be subject to a variance of (+ or -) 10%.

² Tested in accordance with ANSI/RESNA, MC Vol2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

³ Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.

⁴ Battery weight may vary based on battery manufacturer.

⁵ Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.



MOBILITY

movemobility.com.au